



FILTER FABRIC FENCE NOTES:

1. FILTER FABRIC FENCES SHALL BE INSTALLED ALONG CONTOURS WHENEVER POSSIBLE.
2. FILTER FABRIC SHALL BE PURCHASED IN A CONTINUOUS ROLL CUT TO THE LENGTH OF THE BARRIER TO AVOID USE OF JOINTS. WHEN JOINTS ARE NECESSARY, FILTER FABRIC SHALL BE SPLICED AT POSTS WITH A MINIMUM 6-INCH OVERLAP. USE STAPLES, WIRE RINGS, OR EQUIVALENT TO ATTACH FABRIC TO POSTS.
3. INSTALL FILTER FABRIC ACCORDING TO THE MANUFACTURER'S SPECIFICATIONS.
4. INSTALL THE ENDS OF THE FILTER FABRIC FENCE TO POINT SLIGHTLY UPSLOPE TO PREVENT SEDIMENT FROM FLOWING AROUND THE ENDS OF THE FENCE.
5. FILTER FABRIC FENCES SHALL BE REMOVED WHEN THEY HAVE SERVED THEIR USEFUL PURPOSE, BUT NOT BEFORE THE UPSLOPE AREA HAS BEEN PERMANENTLY STABILIZED.
6. FILTER FABRIC FENCES SHALL BE INSPECTED IMMEDIATELY AFTER EACH RAINFALL AND AT LEAST DAILY DURING PROLONGED RAINFALL. ANY REQUIRED REPAIRS SHALL BE MADE IMMEDIATELY.
7. WHEN SEWER SERVICES CROSS FILTER FABRIC FENCE, SERVICE TRENCH, DITCH SECTION, AND FILTER FABRIC FENCE SHALL BE RESTORED IMMEDIATELY.
8. TEMPORARY EROSION AND SEDIMENT CONTROL MEASURES SHALL MEET OR EXCEED ALL APPLICABLE PERMIT REQUIREMENTS. ADHERENCE TO THIS DETAIL DOES NOT RELIEVE THE CONTRACTOR FROM PROJECT PERMIT REQUIREMENTS.



FILTER FABRIC FENCE

REVISION DATE FEBRUARY 7, 2023	SCALE NTS	DISTRICT APPROVAL <i>Gregory G. Hill, P.E.</i>	DATE APPROVED APRIL 27, 2023
FILE NAME W-31.DWG			DWG. NO. W-31